

PROXES® RA1

DOT COMPETITION TIRE

The design and components of the Proxes RA1 came from our experience in winning races all over the world. This DOT competition tire* is well known by road racers for delivering quick lap times, consistency, and long wear. Full 8/32" tread depth provides good competitive wet traction, while shaving to 4/32" improves dry traction.

*Caution: Recommended for competition events only.

POPULAR FITMENTS

Race-prepared vehicles such as:

BMW e30
Honda CRX
Honda Civic
Honda S2000

UTQG

100 AA A

SOFT BUT DURABLE R-COMPOUND

- Improves grip for better competitive handling and performance.

STEPPED TREAD DESIGN

- Increased tread area and limited void improves dry traction.
- Groove arrangement assists with wet traction.

TREAD DEPTH INDICATORS

- Allows for more accurate tread depth measurement near the shoulders.



Toyo Tires and the Proxes RR are the official tire of NASA and the spec tire of record in numerous classes.



For the latest tire information, please visit toyotires.com

TOYO TIRES®

PROXES® RA1

PROXES® RA1

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
13	205/60R13	86V	SL	BSW	236700	5.5-(6.0)-7.5	20	8	22.7	8.2	1158	44	970
15	205/50R15	-	SL	BSW	236840	5.5-(6.5)-7.5	20	8	23.1	8.4	1135	44	899
	225/45R15	-	SL	BSW	236970	7.0-(7.5)-8.5	23	8	22.9	9.0	1201	44	908
	225/50R15	-	SL	BSW	236830	6.0-(7.0)-8.0	23	8	23.9	9.2	1323	44	869
16	225/50R16	-	SL	BSW	236890	6.0-(7.0)-8.0	23	8	24.9	9.2	1390	44	835
	245/45R16	-	SL	BSW	236800	7.5-(8.0)-9.0	25	8	24.7	9.6	1477	44	843
	P255/50R16	-	SL	BSW	236880	7.0-(8.0)-9.0	27	8	26.1	10.4	1687	44	797
17	235/40R17	-	SL	BSW	236760	8.0-(8.5)-9.5	24	8	24.4	9.6	1323	44	852
	255/40R17	-	SL	BSW	236770	8.5-(9.0)-10.0	26	8	25	10.4	1477	44	828
	275/40R17	-	SL	BSW	236780	9.0-(9.5)-11.0	29	8	25.7	10.9	1653	44	809
18	275/35R18	-	SL	BSW	236710	9.0-(9.5)-11.0	30	8	25.6	10.9	1521	44	812



SETUP GUIDELINES

TOYO TIRES RECOMMENDS THE FOLLOWING GENERAL SETUP GUIDELINES FOR THE PROXES RA1:

- Operating Temperature: 160°F to 220°F
- Hot Inflation Pressures: High 30s to Low 40s (PSI)
- Camber: -2.5° to -5.0°
- Caster: As much positive as possible

Speed rated "V" = 149mph. "SL" = Standard Load, "BSW" = Black Sidewall. Bold designates measuring rim width. **Inflated dimensions.

For the latest tire information, please visit toyotires.com

