

DOT COMPETITION TIRE

The Proxes R888R is an evolution of the race-winning Proxes R888, delivering even faster lap times and better dry handling. The credit goes to a new tread design and an improved contact patch that puts more rubber on the track. Racers will also appreciate the predictable handling and how quickly the Proxes R888R reaches optimal operating temperature.

*Caution: Recommended for competition events only.

POPULAR FITMENTS

BMW 3-Series
BMW 4-Series
Chevrolet Corvette
Porsche Cayman
Porsche 911

UTQG

100 AA A

HIGH-GRIP RACE COMPOUND

- Reaches optimal operating temperature quickly and provides consistent performance.
- Improves grip for excellent cornering performance.

OPTIMIZED CONTACT PATCH

- Improves dry traction in braking, acceleration, and cornering.

LARGE TREAD BLOCKS ON OUTSIDE TREAD

- Maximizes lateral grip for improved cornering.

WIDE CENTER RIB

- Improves directional stability and precise steering response.

WATER EVACUATION CHANNEL

- Assists with wet traction.

SETUP GUIDELINES

TOYO TIRES RECOMMENDS THE FOLLOWING GENERAL SETUP GUIDELINES FOR THE PROXES R888R:

- Operating Temperature: 160°F to 220°F
- Hot Inflation Pressures: 32 to 38 (psi)
- Camber: -1° to -3°
- Caster: As much positive as possible



PROXES® R888R™



WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
13	185/60R13	80V	SL	BSW	103180	5.0-(5.5)-6.5	17	6.3	21.7	7.4	992	51	956
	205/60R13	86V	SL	BSW	103200	5.5-(6.0)-7.5	20	6.3	22.7	8.2	1168	51	916
	225/45R13	84V	SL	BSW	104530	7.0-(7.5)-8.5	19	6.3	20.9	8.9	1102	51	992
14	185/60R14	82V	SL	BSW	103190	5.0-(5.5)-6.5	19	6.3	22.8	7.4	1047	51	913
15	195/50R15	82V	SL	BSW	102740	5.5-(6.0)-7.0	19	6.3	22.7	7.9	1047	51	914
	195/55R15	85V	SL	BSW	103520	5.5-(6.0)-7.0	20	6.3	23.4	7.9	1135	51	887
	195/55R15	89V	XL	BSW	109820	5.5-(6.0)-7.0	20	6.3	23.4	7.9	1279	50	887
	205/50ZR15	89W	XL	BSW	107710	5.5-(6.5)-7.5	21	6.3	23.1	8.4	1279	50	899
	225/45ZR15	87W	SL	BSW	104470	7.0-(7.5)-8.5	21	6.3	23	8.9	1201	51	905
	225/50ZR15	91W	SL	BSW	103510	6.0-(7.0)-8.0	23	6.3	23.9	9.2	1356	51	869
	235/50ZR15	94W	SL	BSW	104320	6.5-(7.5)-8.5	23	6.3	24.3	9.6	1477	51	855
	195/50ZR16	84W	SL	BSW	103500	5.5-(6.0)-7.0	20	6.3	23.7	7.9	1102	51	876
	205/45ZR16	83W	SL	BSW	103800	6.5-(7.0)-7.5	21	6.3	23.2	8.1	1074	51	894
205/45ZR16	87W	XL	BSW	107740	6.5-(7.0)-7.5	21	6.3	23.2	8.1	1201	50	894	
205/50ZR16	87W	SL	BSW	103810	5.5-(6.5)-7.5	22	6.3	24.1	8.4	1201	51	862	
205/55ZR16	94W	XL	BSW	104310	5.5-(6.5)-7.5	23	6.3	24.9	8.4	1477	50	835	
225/45ZR16	89W	SL	BSW	103530	7.0-(7.5)-8.5	23	6.3	23.9	8.9	1279	51	868	
225/45ZR16	93W	XL	BSW	107750	7.0-(7.5)-8.5	23	6.3	23.9	8.9	1433	50	868	
245/45ZR16	94W	SL	BSW	104330	7.5-(8.0)-9.0	24	6.3	24.6	9.6	1477	51	843	
255/50ZR16	99W	SL	BSW	104480	7.0-(8.0)-9.0	28	6.3	26.1	10.4	1709	51	797	
17	205/40ZR17	80W	SL	BSW	103540	7.0-(7.5)-8.0	20	6.3	23.5	8.3	992	51	885
	205/40ZR17	84W	XL	BSW	104740	7.0-(7.5)-8.0	21	6.3	23.5	8.3	1102	50	885
	205/45ZR17	88W	XL	BSW	104540	6.5-(7.0)-7.5	22	6.3	24.3	8.1	1235	50	857
	205/45ZR17	84W	SL	BSW	103850	6.5-(7.0)-7.5	22	6.3	24.3	8.1	1102	51	857
	205/50ZR17	89W	SL	BSW	103820	5.5-(6.5)-7.5	23	6.3	25.1	8.4	1279	51	827
	215/45ZR17	91W	XL	BSW	104660	(7.0)-8.0	23	6.3	24.6	8.4	1356	50	843
	225/45ZR17	94W	XL	BSW	106910	7.0-(7.5)-8.5	24	6.3	25	8.9	1477	50	832
	235/40ZR17	90W	SL	BSW	103410	8.0-(8.5)-9.5	24	6.3	24.4	9.5	1323	51	851
	235/40ZR17	94W	XL	BSW	106970	8.0-(8.5)-9.5	23	6.3	24.4	9.5	1477	50	851
	235/45ZR17	94W	SL	BSW	103860	7.5-(8.0)-9.0	25	6.3	25.4	9.3	1477	51	819
	245/40ZR17	91W	SL	BSW	104510	8.0-(8.5)-9.5	25	6.3	24.7	9.8	1356	51	840
	255/40ZR17	98W	XL	BSW	109530	8.5-(9.0)-10.0	26	6.3	25	10.2	1653	50	830
	255/40ZR17	94W	SL	BSW	103880	8.5-(9.0)-10.0	27	6.3	25	10.2	1477	51	830
	275/40ZR17	98W	SL	BSW	104520	9.0-(9.5)-11.0	28	6.3	25.7	10.9	1653	51	809
	315/35ZR17	102W	SL	BSW	104430	10.5-(11.0)-12.5	31	6.3	25.7	12.6	1874	51	809
18	225/40ZR18	92Y	XL	BSW	102700	7.5-(8.0)-9.0	24	6.3	25.1	9.1	1389	50	828
	235/40ZR18	95Y	XL	BSW	104750	8.0-(8.5)-9.5	25	6.3	25.4	9.5	1521	50	818
	245/40ZR18	97Y	XL	BSW	107720	8.0-(8.5)-9.5	29	6.3	25.7	9.8	1609	50	808
	245/40ZR18	93Y	SL	BSW	103870	8.0-(8.5)-9.5	26	6.3	25.7	9.8	1433	51	808
	255/35ZR18	90Y	SL	BSW	103830	8.5-(9.0)-10.0	26	6.3	25	10.2	1323	51	831
	255/35ZR18	94Y	XL	BSW	106980	8.5-(9.0)-10.0	25	6.3	25	10.2	1477	50	831
	265/35ZR18	97Y	XL	BSW	104570	9.0-(9.5)-10.5	27	6.3	25.3	10.7	1609	50	821
	275/35ZR18	95Y	SL	BSW	104260	9.0-(9.5)-11.0	28	6.3	25.6	10.9	1521	51	813
	295/30ZR18	98Y	XL	BSW	104270	10.0-(10.5)-11.0	29	6.3	25	11.9	1653	50	831
	305/35ZR18	105Y	XL	BSW	104460	10.0-(11.0)-12.0	32	6.3	26.4	12.3	2039	50	786
19	315/30ZR18	98Y	SL	BSW	104370	10.5-(11.0)-11.5	31	6.3	25.5	12.6	1653	51	816
	335/30ZR18	102Y	SL	BSW	104340	11.5-(12.0)-12.5	33	6.3	25.9	13.5	1874	51	801
	235/35ZR19	(91Y)	XL	BSW	103840	8.0-(8.5)-9.5	25	6.3	25.5	9.5	1356	50	816
	245/35ZR19	(89Y)	SL	BSW	104440	8.0-(8.5)-9.5	25	6.3	25.8	9.8	1279	51	806
	265/30ZR19	89Y	SL	BSW	104240	9.0-(9.5)-10.0	27	6.3	25.3	10.7	1279	51	821
	265/30ZR19	93Y	XL	BSW	107730	9.0-(9.5)-10.0	27	6.3	25.3	10.7	1433	50	821
	265/35ZR19	(94Y)	SL	BSW	104490	9.0-(9.5)-10.5	29	6.3	26.3	10.7	1477	51	789
	265/40ZR19	(98Y)	SL	BSW	104500	9.0-(9.5)-10.5	30	6.3	27.4	10.7	1653	51	759
	275/35R19	(96Y)	SL	BSW	104420	9.0-(9.5)-11.0	30	6.3	26.6	10.9	1565	51	782
	285/35ZR19	(99Y)	SL	BSW	104450	9.5-(10.0)-11.0	31	6.3	26.9	11.4	1709	51	773
295/30ZR19	100Y	XL	BSW	104280	10.0-(10.5)-11.0	30	6.3	26	11.9	1764	50	798	

Speed rated "V" = 149mph, "W" = 168mph, "Y" = 186mph, "[Y]" = 195mph. "SL" = Standard Load, "XL" = Extra Load. "RD" = Reinforced, "BSW" = Black Sidewall. Bold designates measuring rim width. **Inflated dimensions.

SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX. LOAD (LBS)	MAX. PRESSURE (PSI)	REVS PER MILE
19	305/30ZR19	(102Y)	XL	BSW	104290	10.5- (11.0) -11.5	32	6.3	26.3	12.3	1874	50	791
	325/30ZR19	(101Y)	SL	BSW	104380	11.0- (11.5) -12.0	33	6.3	26.7	13	1819	51	777
	345/30ZR19	(105Y)	SL	BSW	104350	11.5- (12.0) -12.5	36	6.3	27.2	13.8	2039	51	764
20	255/35ZR20	(93Y)	SL	BSW	104400	8.5- (9.0) -10.0	29	6.3	27	10.2	1433	51	769
	285/30ZR20	(95Y)	SL	BSW	104560	9.5- (10.0) -10.5	31	6.3	26.8	11.4	1521	51	776
	285/35ZR20	(100Y)	SL	BSW	104150	9.5- (10.0) -11.0	33	6.3	27.9	11.4	1764	51	745
	305/35ZR20	(104Y)	SL	BSW	104410	10.0- (11.0) -12.0	35	6.3	28.4	12.3	1984	51	731
	315/30ZR20	(101Y)	SL	BSW	104300	10.5- (11.0) -11.5	35	6.3	27.5	12.6	1819	51	756
	325/30ZR20	(102Y)	SL	BSW	104390	11.0- (11.5) -12.0	35	6.3	27.7	13	1874	51	750
20	255/35ZR20	(93Y)	SL	BSW	104400	8.5- (9.0) -10.0	29	6.3	27	10.2	1433	51	769
	285/30ZR20	(95Y)	SL	BSW	104560	9.5- (10.0) -10.5	31	6.3	26.8	11.4	1521	51	776
	285/35ZR20	(100Y)	SL	BSW	104150	9.5- (10.0) -11.0	33	6.3	27.9	11.4	1764	51	745
	305/35ZR20	(104Y)	SL	BSW	104410	10.0- (11.0) -12.0	35	6.3	28.4	12.3	1984	51	731
	315/30ZR20	(101Y)	SL	BSW	104300	10.5- (11.0) -11.5	35	6.3	27.5	12.6	1819	51	756
	325/30ZR20	(102Y)	SL	BSW	104390	11.0- (11.5) -12.0	35	6.3	27.7	13	1874	51	750

SPORTS CAR / COMPETITION

S