

DOT COMPETITION TIRE

The Proxes R888 is for drivers who know what it means to really push a car. Its optimized construction and tread design balances dry performance and wet traction, keeping you fully under control in extreme driving situations. If your idea of fun includes road racing, track days, and high performance driving schools, then this DOT competition tire* is for you.

*Caution: Recommended for competition events only.

POPULAR FITMENTS

Race-prepared vehicles such as:
BMW 3-Series
Mazda Miata
Nissan GT-R
Subaru WRX

UTQG

100 AA A

ENHANCED R-COMPOUND TREAD

- Maximizes grip for better competitive handling and performance.

UNIDIRECTIONAL V-SHAPED TREAD DESIGN

- Increased tread area and limited void improve dry traction.
- V-shaped grooves assist with wet traction.

CONTINUOUS CENTER CONTACT

- Increases braking performance and dry traction.

SEMI-SLICK SHOULDER AREA

- Improves grip for better steering response.

STIFF BEAD CONSTRUCTION AND WIDER TREAD WIDTH

- Increases cornering force for better competitive handling.

SETUP GUIDELINES

TOYO TIRES RECOMMENDS THE FOLLOWING GENERAL SETUP GUIDELINES FOR THE PROXES R888:

- Operating Temperature: 160°F to 220°F
- Hot Inflation Pressures: 32 to 38 (psi)
- Camber: -1° to -3°
- Caster: As much positive as possible



SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX. LOAD (LBS)	MAX. PRESSURE (PSI)	REVS PER MILE
14	205/55R14	85V	SL	BSW	168060	5.5- (6.5) -7.5	20	6.3	22.8	8.4	1135	51	911
	225/50R14	89V	SL	BSW	168070	6.0- (7.0) -8.0	21	6.3	22.8	9.3	1279	51	910
16	225/50ZR16	92W	SL	BSW	168150	6.0- (7.0) -8.0	24	6.3	24.7	9.3	1389	51	840
	255/50ZR16	99W	SL	BSW	168050	7.0- (8.0) -9.0	27	6.4	25.9	10.6	1709	51	803
18	275/40ZR18	99W	SL	BSW	168110	9.0- (9.5) -11.0	29	6.4	26.7	11	1709	51	779
	285/30ZR18	97Y	RD	BSW	168250	9.5- (10.0) -10.5	28	6.3	24.8	11.3	1609	50	836

SPORTS CAR / COMPETITION

S

Speed rated "V" = 149mph, "W" = 168mph, "Y" = 186mph, "[Y]" = 195mph. "SL" = Standard Load, "RD" = Reinforced, "BSW" = Black Sidewall. Bold designates measuring rim width. **Inflated dimensions.

For the latest tire information, please visit toyotires.com.

TOYO TIRES®