

## DOT COMPETITION TIRE

Race-ready off the shelf with a 4/32" deep tread, the Proxes RR delivers consistent lap times and predictable handling on dry tracks. This DOT competition tire\* is ideal for NASA road racing, track days, and high performance driving schools. The symmetric two-groove tread design and special tread compound provide a maximum contact patch and ultimate dry traction with superior cornering force.

\*Warning: For racing purposes only. Not for highway use.

### POPULAR FITMENTS

Race-prepared vehicles in NASA SPEC classes:  
American Iron  
Honda Challenge  
Spec E30  
Spec Miata  
Spec 944

### UTQG

40 C A



Toyo Tires and the Proxes RR are the official tire of NASA and the spec tire of record in numerous classes.

### RACING TREAD COMPOUND

- Increases grip and improves lap times.

### REINFORCED SIDEWALL AND HIGH-MODULUS BEAD FILLER

- Provides excellent steering response and feedback.

### WEAR INSPECTION HOLES

- Provides easy tread depth measurement from any position.

### SIDEWALL MARKING AREA

- Allows for easy labeling on the sidewall.



# SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX. LOAD (LBS)	MAX. PRESSURE (PSI)	REVS PER MILE
13	205/60R13	86V	SL	BSW	255150	5.5-( <b>6.0</b> )-7.5	19	3.7	22.7	8.2	1168	51	916
	205/50ZR15		SL	BSW	255000	5.5-( <b>6.5</b> )-7.5	20	3.7	23.0	8.5	1168	51	902
15	225/45ZR15		SL	BSW	255140	7.0-( <b>7.5</b> )-8.5	21	3.7	23.0	8.9	1201	51	905
	225/50ZR15		SL	BSW	255080	6.0-( <b>7.0</b> )-8.0	22	3.7	23.9	9.2	1356	51	869
	245/40ZR15		SL	BSW	255240	8.0-( <b>8.5</b> )-9.5	21	3.7	22.7	9.8	1235	51	914
	225/50R16		SL	BSW	255160	6.0-( <b>7.0</b> )-8.0	24	3.7	24.9	9.2	1389	51	835
16	245/45ZR16		SL	BSW	255130	7.5-( <b>8.0</b> )-9.0	23	3.7	24.6	9.6	1477	51	843
	235/45ZR17		SL	BSW	255270	7.0-( <b>7.5</b> )-8.5	23	3.7	25.0	8.9	1356	51	832
17	235/40ZR17		SL	BSW	255120	8.0-( <b>8.5</b> )-9.5	22	3.7	24.4	9.5	1323	51	851
	245/40ZR17		SL	BSW	255260	8.0-( <b>8.5</b> )-9.5	23	3.7	24.7	9.8	1356	51	840
	255/40ZR17		SL	BSW	255110	8.5-( <b>9.0</b> )-10.0	24	3.7	25.0	10.2	1477	51	830
	275/40ZR17		SL	BSW	255100	9.0-( <b>9.5</b> )-11.0	28	3.7	25.7	10.9	1653	51	809
	255/30ZR18		SL	BSW	255300	8.5-( <b>9.0</b> )-10.0	25	3.7	25.0	10.2	1323	51	831
18	P275/35ZR18	87	LL	BSW	255070	9.0-( <b>9.5</b> )-11.0	26	3.7	25.6	10.9	1201	44	813
	285/30ZR18		SL	BSW	255250	9.5-( <b>10.0</b> )-10.5	26	3.7	24.8	11.4	1433	51	839
	295/30ZR18		SL	BSW	255210	10.0-( <b>10.5</b> )-11.0	28	3.7	25.0	11.9	1477	51	831
	P305/35R18		LL	BSW	255170	10.0-( <b>11.0</b> )-12.0	30	3.7	26.4	12.3	1433	44	786
	315/30ZR18		SL	BSW	255180	10.5-( <b>11.0</b> )-11.5	29	3.7	25.5	12.6	1653	51	816
	235/35ZR19		SL	BSW	255230	8.0-( <b>8.5</b> )-9.5	23	3.7	25.5	9.5	1201	51	816
19	295/30ZR19		SL	BSW	255220	10.0-( <b>10.5</b> )-11.0	30	3.7	26.0	11.9	1565	51	798
	345/30ZR19		SL	BSW	255280	11.5-( <b>12.0</b> )-12.5	33	3.7	27.2	13.8	2039	51	764
	255/35ZR20	(93Y)	SL	BSW	255310	8.5-( <b>9.0</b> )-10.0	27	3.7	27.0	10.2	1433	51	769
20	285/30ZR20	(95Y)	SL	BSW	255190	9.5-( <b>10.0</b> )-10.5	29	3.7	26.8	11.4	1521	51	776
	285/35ZR20	(100Y)	SL	BSW	255200	9.5-( <b>10.0</b> )-11.0	32	3.7	27.9	11.4	1764	51	745
	315/30ZR20	(101Y)	SL	BSW	255320	10.5-( <b>11.0</b> )-11.5	33	3.7	27.5	12.6	1819	51	756
	325/30ZR20	(102Y)	SL	BSW	255330	11.0-( <b>11.5</b> )-12.0	34	3.7	27.7	13.0	1874	51	750

## SETUP GUIDELINES

TOYO TIRES RECOMMENDS THE FOLLOWING GENERAL SETUP GUIDELINES FOR THE PROXES RR:

- Operating Temperature: 160°F to 220°F
- Hot Inflation Pressures: High 30s to Low 40s (PSI)
- Camber: -2.5° to -5.0°
- Caster: As much positive as possible