

DOT COMPETITION TIRE

The design and components of the Proxes RA1 came from our experience in winning races all over the world. This DOT competition tire* is well-known by road racers for delivering quick lap times, consistency, and long wear. Full 8/32" tread depth provides good competitive wet traction, while shaving to 4/32" improves dry traction.

*Caution: Recommended for competition events only.

POPULAR FITMENTS

Race-prepared vehicles such as:
BMW E30
Honda Civic
Honda CRX
Honda S2000
Mazda Miata MX-5

UTQG

100 AA A



Toyo Tires is the official tire of NASA and the spec tire of record in numerous classes.

SOFT BUT DURABLE R-COMPOUND

- Improves grip for better competitive handling and performance.

STEPPED TREAD DESIGN

- Increased tread area and limited void improves dry traction.
- Groove arrangement assists with wet traction.

TREAD DEPTH INDICATORS

- Allows for more accurate tread depth measurement near the shoulders.



SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX. LOAD (LBS)	MAX. PRESSURE (PSI)	REVS PER MILE
13	205/60R13	86V	SL	BSW	236700	5.5- (6.0) -7.5	20	8.0	22.7	8.2	1158	44	970
	205/50ZR15		SL	BSW	236840	5.5- (6.5) -7.5	20	8.0	23.1	8.4	1135	44	899
15	225/45ZR15		SL	BSW	236970	7.0- (7.5) -8.5	23	8.0	22.9	9	1201	44	908
	225/50ZR15		SL	BSW	236830	6.0- (7.0) -8.0	23	8.0	23.9	9.2	1323	44	869
	225/50ZR16		SL	BSW	236890	6.0- (7.0) -8.0	23	8.0	24.9	9.2	1390	44	835
16	245/45ZR16		SL	BSW	236800	7.5- (8.0) -9.0	25	8.0	24.7	9.6	1477	44	843
	P255/50ZR16		SL	BSW	236880	7.0- (8.0) -9.0	27	8.0	26.1	10.4	1687	44	797
	235/40ZR17		SL	BSW	236760	8.0- (8.5) -9.5	24	8.0	24.4	9.6	1323	44	852
17	255/40ZR17		SL	BSW	236770	8.5- (9.0) -10.0	26	8.0	25	10.4	1477	44	828
	275/40ZR17		SL	BSW	236780	9.0- (9.5) -11.0	29	8.0	25.7	10.9	1653	44	809
18	275/35ZR18		SL	BSW	236710	9.0- (9.5) -11.0	30	8.0	25.6	10.9	1521	44	812

SPORTS CAR / COMPETITION

S

SETUP GUIDELINES

TOYO TIRES RECOMMENDS THE FOLLOWING GENERAL SETUP GUIDELINES FOR THE PROXES RA1:

- Operating Temperature: 160°F to 220°F
- Hot Inflation Pressures: High 30s to Low 40s (PSI)
- Camber: -2.5° to -5.0°
- Caster: As much positive as possible

Speed rated "V" = 149mph. "SL" = Standard Load, "BSW" = Black Sidewall. Bold designates measuring rim width. **Inflated dimensions.

For the latest tire information, please visit toyotires.com.