

Tire Size	Load Rating	Speed Rating	Load Range	Overall Tire Diameter (in.)	Circ. (in.)	Tread Width (in.)	Section width (in.)	Design Rim Width (in.)	Tread Depth (32nd in.)	Tire Weight (lbs)	Approved Rim Widths (in.)	Max. Inflation Pressure (psi)	Revs Per Mile	UTQG
205/50 R 15	89	V	XL	23.1	72.6	7.1	8.4	6.5	7	18.3	(5.5 - 7.5)	51	900	200 A A
225/45 R 15	87	V	SL	22.8	71.6	7.8	9.2	7.5	7	23.0	(7.0 - 8.5)	51	904	200 A A
225/40 ZR 17	90	W	XL	24.1	75.7	7.9	9.3	8	7	21.0	(7.5 - 9.0)	51	862	200 A A
225/45 ZR 17	94	W	XL	25.1	78.7	7.8	9.2	7.5	7	21.4	(7.0 - 8.5)	51	832	200 A A
245/40 ZR 17	95	W	XL	24.8	77.8	8.6	10.0	8.5	7	23.1	(8.0 - 9.5)	51	840	200 A A
255/40 ZR 17	98	W	XL	25.1	78.7	8.9	10.5	9	7	24.3	(8.5 - 10.0)	51	830	200 A A
245/35 ZR 18	92	W	XL	24.8	77.8	8.7	10.1	8.5	7	25.7	(8.0 - 9.5)	51	839	200 A A
245/40 ZR 18	97	W	XL	25.8	81.0	8.6	10.0	8.5	7	24.6	(8.0 - 9.5)	51	808	200 A A
275/35 ZR 18	99	W	XL	25.5	80.1	10.0	11.1	9.5	7	26.0	(9.0 - 11.0)	51	812	200 A A
295/30 ZR 18	98	W	XL	25.0	78.4	10.9	12.1	10.5	7	26.6	(10.0 - 11.0)	51	832	200 A A
315/30 ZR 18	98	W	SL	25.4	79.7	11.7	12.8	11	7	28.8	(10.5 - 11.5)	51	817	200 A A
345/35 ZR 18	109	W	SL	27.5	86.4	12.8	13.8	12	7	26.5	(11.5 - 13.5)	51	755	200 A A
235/35 ZR 19	91	W	XL	25.6	80.2	8.3	9.8	8.5	7	20.6	(8.0 - 9.5)	51	815	200 A A
265/35 ZR 19	98	W	XL	26.3	82.7	9.5	11.0	9.5	7	24.2	(9.0 - 10.5)	51	790	200 A A
295/30 ZR 19	100	W	XL	26.0	81.7	10.9	12.1	10.5	7	27.0	(10.0 - 11.0)	51	800	200 A A
315/30 ZR 19	104	W	XL	26.6	83.4	11.7	12.7	11	7	27.0	(10.5 - 11.5)	51	786	200 A A
325/30 ZR 19	105	W	XL	26.7	83.8	12.0	13.1	11.5	7	27.0	(11.0 - 12.0)	51	779	200 A A
345/30 ZR 19	109	W	XL	27.1	85.2	12.8	13.8	12	7	27.0	(11.5 - 12.5)	51	765	200 A A