

Size	Load/Speed	Load ID	Tread Depth	Product Code	Approved rim range	Inflated OD mm.	Inflated OD in.	Inflated Section mm.	Inflated Section in.	Inflated tread mm	Inflated tread in.	Max Load [kg/lb]	Max Pressure	UTQG	Weight [lb]
275/35ZR18	97Y	XL	5.3	47836	9-11	650	25.6	278	10.9	252	9.9	775/1709	51	200 A A	22.4
295/30ZR18	102(Y)	XL	5.3	47840	10-11	643	25.3	300	11.8	276	10.9	750/1653	51	200 A A	23.2
315/30ZR18	(Y)	SL	5.3	47854	10.5-11.5	651	25.6	318	12.5	305	12.0	750/1653	51	200 A A	24.4
265/35ZR19	93(Y)	XL	5.3	47924	9-10.5	668	26.3	276	10.9	242	9.5	750/1653	51	200 A A	21.6
275/35ZR19	100(Y)	XL	5.3	47930	9-11	681	26.8	277	10.9	247	9.7	800/1764	51	200 A A	22.4
285/35ZR19	104(Y)	XL	5.3	47934	9.5-11	688	27.1	289	11.4	258	10.2	875/1929	51	200 A A	24.6
305/30ZR19	(Y)	XL	5.3	47944	10.5-11.5	670	26.4	314	12.4	279	11.0	850/1874	51	200 A A	24.4
325/30ZR19	(Y)	XL	5.3	47950	11-12	683	26.9	329	13.0	306	12.0	925/2039	51	200 A A	26.3
285/30ZR20	103(Y)	XL	5.3	47970	9.5-10.5	689	27.1	284	11.2	261	10.3	775/1709	51	200 A A	23.7



